



Vinyl Tape 471 • 4712 (Linered) Unfinished International Log Rolls

Technical Bulletin

Date: September 2019

Supersedes: NEW

Description

3M™ Vinyl Tape 471 and 4712 are conformable colored (9 colors plus transparent) tapes made from vinyl backing with rubber adhesive. They are ideal for many lane and safety markings, colour coding, abrasion protection, masking, sealing, splicing and other general purpose applications.

3M vinyl tape 4712 is a lined version of 3M vinyl tape 471 that may be used for die cutting or large area applications.

Product Construction

Product	Adhesive	Color
Vinyl Tape 471	Rubber	Yellow, white, red, black, brown, green, orange, purple, blue and transparent
Vinyl Tape 4712	Rubber	Yellow, white, red, black, brown, green, orange, purple, blue and transparent

Typical Unfinished International Log Roll Dimensions

Actual final dimensional values will vary due to the natural shrinkage of Polyvinyl Chloride film with time.	
Properties for all colours:	
Maximum Manufactured Film Width	125.1 cm
Overall Film Width Range	120.0 cm to 125.1 cm
Usable Film Width Range	120.0 cm to 122.6 cm

Storage & Shelf Life

Store under normal conditions of 16 ° to 27 °C and 40 to 60 % relative humidity, in the original carton.

To obtain best performance, use this product within 18 months from date of manufacture.

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.

This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company

Industrial Adhesives & Tapes Division
3M Belgium
Hermeslaan 7
1831 Diegem
Belgium

Industrial Adhesives & Tapes Division
3M Nederland
Molengraafsingel 29
2629 JD Delft
Nederland